

ABB BALDOR RELIANCE III

Customer information packet

SPJMM3311T-G

7.5HP, 1775RPM, 3PH, 60HZ, 213JM, 3750M, OPSB

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	213JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	10.000 A @ 460.0 V 20.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	92.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	10.0 a
Insulation Class	H
Inverter Code	Inverter Duty

Part Detail

Revision	A
Type	AC
Mech. spec.	37EE004
Base	
Status	PRD/A
Elec. spec.	37WGZ670
Layout	37LYEE004
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	04
Leads	9#14
Proprietary	False
Created date	08-14-2025

KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3750M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	20.07 IN
Power Factor	78
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.25
Shaft Diameter	0.875 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L														
CAT #	SPJMM3311T-G					WGT	158	LBS						
SPEC	37EE004Z670					ENCL	OPSB							
SER #						CC	010A	IP	23					
HP	7.5				MAG CUR	9.8/4.9								
VOLTS	230/460					NEMA NOM. EFF				92.4				
AMPS	20/10						PF	78						
RATING	40C AMB-CONT													
RPM	1775					MAX RPM		2700						
FRAME	213JM	HZ	60			CODE	L	CLASS	H					
SER.F.	1.25	SF AMP	23.8/11.9				PH	3	DES	A				
DE	6309		ODE		6206									
LUBRICATION	POLYREX EM													
ID LOGO	INVERTER TYPE				VPWM		CHP	60	TO	90	1.5:1			
ID LOGO	WK2	1.18	CT	6	TO	60	10:1							
ID LOGO	SL HZ	0.8	VT	3	TO	60	20:1							
							QR							
YR														

AC Induction Motor Performance Data

Record # 112297

Typical performance - not guaranteed values

Winding: 37WGZ670-R004			Type: 3750M		Enclosure: OPSB	
Nameplate Data			460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		7.5	Full Load Torque		22.31 LB-FT	
Volts		230/460	Start Configuration		direct on line	
Full Load Amps		20/10	Breakdown Torque		84.6 LB-FT	
R.P.M.		1775	Pull-up Torque		42.8 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		54.6 LB-FT
NEMA Design Code		A	KVA Code	Starting Current		88.8 A
Service Factor (S.F.)		1.25	No-load Current		4.93 A	
NEMA Nom. Eff.		92.4	Power Factor	Line-line Res. @ 25°C		1.12 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		25°C
S.F. Amps		23.8/11.9		Temp. Rise @ S.F. Load		33°C
				Locked-rotor Power Factor		35.9
				Rotor inertia		1.23 lb-ft²

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	59	72	78	82	84	82
Efficiency	87.4	91.9	92.8	92.7	92.1	91.4	92.1
Speed	1794	1789	1783	1778	1772	1765	1772
Line amperes	5.39	6.48	7.98	9.73	11.7	13.8	11.7

ABB Motors and Mechanical Inc.

WINDING # 37WGZ670

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 1775 RPM 460 V 3750M

TORQUES (LB-FT): PO=84.6 PU=42.8 LR=54.6 LRA=88.8





