

ABB BALDOR RELIANCE III

Customer information packet

SPJMM3555T-G

2HP, 3475RPM, 3PH, 60HZ, 145JM, 3532M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	145JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.400 A @ 460.0 V 4.800 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.4 a
Insulation Class	H

Part Detail

Revision	A
Type	AC
Mech. spec.	35EE455
Base	
Status	PRD/A
Elec. spec.	35WGK113
Layout	35LYEE455
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	07-30-2025

Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	6000 rpm
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3532M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.28 IN
Power Factor	89
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.875 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3475 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L														
CAT #	SPJMM3555T-G					WGT	50	LBS						
SPEC	35EE455K113					ENCL	TEFC							
SER #						CC	010A	IP	54					
HP	2					MAG CUR	1.8/9							
VOLTS	230/460					NEMA NOM. EFF							86.5	
AMPS	4.8/2.4					PF	89							
RATING	40C AMB-CONT													
RPM	3475					MAX RPM				6000				
FRAME	145JM	HZ	60		CODE		L	CLASS			H			
SER.F.	1.25	SF AMP	6/3				PH	3	DES	B				
DE	6206		ODE		6203									
LUBRICATION	POLYREX EM													
ID LOGO	INVERTER TYPE				VPWM		CHP	60	TO		90	1.5:1		
ID LOGO	WK2	0.09	CT	6	TO	60	10:1							
ID LOGO	SL HZ	2.1	VT	3	TO	60	20:1							
							QR							
YR														

AC Induction Motor Performance Data

Record # 109563

Preliminary Data Sheet

Winding: 35WGK113-R004			Type: 3532M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		2	Full Load Torque		3.01 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		4.8/2.4	Breakdown Torque		12.6 LB-FT		
R.P.M.		3475	Pull-up Torque		7.1 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		10.9 LB-FT	
NEMA Design Code		B	KVA Code		L		
Service Factor (S.F.)		1.25	Starting Current		24.5 A		
NEMA Nom. Eff.		86.5	Power Factor		89		
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		51°C
S.F. Amps		6/3			Temp. Rise @ S.F. Load		68°C
					Locked-rotor Power Factor		47.3
					Rotor inertia		0.0885 lb-ft²

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	55	76	84	89	91	92	91
Efficiency	78.9	86.2	87	87.1	85.8	84.4	85.8
Speed	3568	3538	3508	3476	3439	3400	3439
Line amperes	1.06	1.46	1.91	2.41	3	3.61	3

ABB Motors and Mechanical Inc.

WINDING # 35WGK113

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 3475 RPM 460 V 3532M

TORQUES (LB-FT): PO=12.6 PU=7.1 LR=10.9 LRA=24.5





