

ABB BALDOR RELIANCE III

Customer information packet

SPJPM3713T

15HP, 3515RPM, 3PH, 60HZ, 215JP, 3756M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	215JP
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	17.000 A @ 460.0 V 34.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	92.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	17.0 a
Insulation Class	F
Inverter Code	Inverter Duty

Part Detail

Revision	A
Type	AC
Mech. spec.	37EE007
Base	
Status	PRD/A
Elec. spec.	37WGR601
Layout	37LYEE007
Eff. date	11-19-2025
CD Diagram	CD0180
Poles	02
Leads	9#14
Proprietary	False
Created date	08-14-2025

KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3756M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	26.26 IN
Power Factor	88
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	1.250 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3515 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A05L													
CAT #	SPJPM3713T					WGT	187	LBS					
SPEC	37EE007R601					ENCL	TEFC						
SER #						CC	010A	IP	54				
HP	15	MAG CUR				11.6/5.8							
VOLTS	230/460					NEMA NOM. EFF					92.4		
AMPS	34/17					PF	88						
RATING	40C AMB-CONT												
RPM	3515					MAX RPM		5400					
FRAME	215JP	HZ	60	CODE		K	CLASS		F				
SER.F.	1.25	SF AMP	42.4/21.2				PH	3	DES	A			
DE	6309		ODE		6206								
LUBRICATION	POLYREX EM												
ID LOGO	INVERTER TYPE			VPWM		CHP	60	TO		90	1.5:1		
ID LOGO	WK2	0.51	CT	6	TO	60	10:1						
ID LOGO	SL HZ	1.4	VT	3	TO	60	20:1						

AC Induction Motor Performance Data

Record # 116896

Typical performance - not guaranteed values

Winding: 37WGR601-R010			Type: 3756M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		15	Full Load Torque		22.09 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		34/17	Breakdown Torque		112 LB-FT		
R.P.M.		3515	Pull-up Torque		43.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		62 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		161 A
Service Factor (S.F.)		1.25	No-load Current		5.75 A		
NEMA Nom. Eff.		92.4	Power Factor	88	Line-line Res. @ 25°C		0.406 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		63°C
S.F. Amps		42.4/21.2	Temp. Rise @ S.F. Load		88°C		
			Locked-rotor Power Factor		29.9		
			Rotor inertia		0.51 lb-ft²		

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	53	76	85	88	90	90	90
Efficiency	89.4	92.8	93.2	92.7	91.9	90.8	91.9
Speed	3580	3561	3539	3516	3491	3465	3491
Line amperes	6.81	9.54	13.1	16.95	20.9	25.31	20.9


ABB Motors and Mechanical Inc.


WINDING # 37WGR601

Typical performance - not guaranteed values.


15 HP 3 PH 60 HZ 3515 RPM 460 V 3756M

TORQUES (LB-FT): PO=112 PU=43.2 LR=62 LRA=161







CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1