

ABB BALDOR RELIANCE III

Customer information packet

SPM2515T

20HP, 1775RPM, 3PH, 60HZ, 256T, 3976M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	256T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	20.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM 4 WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	24.000 A @ 460.0 V 48.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.1 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	24.0 a

Part Detail

Revision	D
Type	AC
Mech. spec.	39E761
Base	
Status	PRD/A
Elec. spec.	39WGY451
Layout	39LYE761
Eff. date	12-15-2025
CD Diagram	CD0180
Poles	04
Leads	9#10
Proprietary	False
Created date	09-05-2023

Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3976M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	25.21 IN
Power Factor	84
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

NP4423A01A05L												
CAT #	SPM2515T					WGT	436	LBS				
SPEC	39E761Y451					ENCL	OPSB					
SER #						CC	010A	IP	23			
HP	20	MAG CUR				19.6/9.8						
VOLTS	230/460					NEMA NOM. EFF						94.1
AMPS	48/24					PF	84					
RATING	40C AMB-CONT											
RPM	1775					MAX RPM			2700			
FRAME	256T	HZ	60	CODE		J	CLASS			F		
SER.F.	1.25	SF AMP	58/29				PH	3	DES	A		
DE	6309		ODE		6208							
LUBRICATION	POLYREX EM											
ID LOGO	INVERTER TYPE			VPWM		CHP	60	TO		90	1.5:1	
ID LOGO	WK2	3.32	CT	6	TO	60	10:1					
ID LOGO	SL HZ	0.8	VT	3	TO	60	20:1					
						QR						
YR												

AC Induction Motor Performance Data

Record # 109528

Typical performance - not guaranteed values

Winding: 39WGY451-R004			Type: 3976M		Enclosure: OPSB		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		20		Full Load Torque		59.28 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		48/24		Breakdown Torque		237 LB-FT	
R.P.M.		1775		Pull-up Torque		122 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		129 LB-FT	
NEMA Design Code		A	KVA Code	J	Starting Current		212 A
Service Factor (S.F.)		1.25		No-load Current		10.3 A	
NEMA Nom. Eff.		94.1	Power Factor	84	Line-line Res. @ 25°C		0.287 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		31°C	
S.F. Amps		54/27		Temp. Rise @ S.F. Load		41°C	
				Locked-rotor Power Factor		29.4	
				Rotor inertia		3.32 lb-ft²	

Load Characteristics 460 V, 60 Hz, 20 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	67	78	83	86	88	86
Efficiency	89.1	93.2	94	94.1	93.8	93.3	93.8
Speed	1794	1788	1782	1776	1769	1762	1769
Line amperes	11.8	15	19.2	23.9	28.9	34.4	28.9


ABB Motors and Mechanical Inc.

WINDING # 39WGY451


Typical performance - not guaranteed values.

20 HP 3 PH 60 HZ 1775 RPM 460 V 3976M


TORQUES (LB-FT): PO=237 PU=122 LR=129 LRA=212




10/7/2026 ACPERF, record # 109528




CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1