

ABB BALDOR RELIANCE III

Customer information packet

SPM3314T-G

15HP, 3515RPM, 3PH, 60HZ, 215T, 3756M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	215T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	17.000 A @ 460.0 V 34.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	92.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	17.0 a
Insulation Class	F

Part Detail

Revision	A
Type	AC
Mech. spec.	37T743
Base	
Status	PRD/A
Elec. spec.	37WGR601
Layout	37LYT743
Eff. date	11-19-2025
CD Diagram	CD0180
Poles	02
Leads	9#14
Proprietary	False
Created date	04-03-2025

Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3756M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	18.95 IN
Power Factor	88
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	1.375 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3515 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L														
CAT #	SPM3314T-G					WGT	187	LBS						
SPEC	37T743R601					ENCL	OPSB							
SER #						CC	010A	IP	23					
HP	15	MAG CUR				11.6/5.8								
VOLTS	230/460					NEMA NOM. EFF					92.4			
AMPS	34/17					PF	88							
RATING	40C AMB-CONT													
RPM	3515					MAX RPM		5400						
FRAME	215T	HZ	60	CODE		K	CLASS		H					
SER.F.	1.25	SF AMP	41.8/20.9				PH	3	DES	A				
DE	6307		ODE		6206									
LUBRICATION	POLYREX EM													
ID LOGO	INVERTER TYPE			VPWM		CHP	60	TO		90	1.5:1			
ID LOGO	WK2	0.51	CT	6	TO	60	10:1							
ID LOGO	SL HZ	1.4	VT	3	TO	60	20:1							
							QR							
YR														

AC Induction Motor Performance Data

Record # 112293

Preliminary Data Sheet

Winding: 37WGR601-R008			Type: 3756M		Enclosure: ODP		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		15	Full Load Torque		22.09 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		34/17	Breakdown Torque		112 LB-FT		
R.P.M.		3515	Pull-up Torque		43.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		62 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		161 A
Service Factor (S.F.)		1.25	No-load Current		5.75 A		
NEMA Nom. Eff.		92.4	Power Factor	88	Line-line Res. @ 25°C		0.406 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		63°C
S.F. Amps		41.8/20.9	Temp. Rise @ S.F. Load		85°C		
			Locked-rotor Power Factor		29.9		
			Rotor inertia		0.51 lb-ft²		

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	53	76	85	88	90	90	90
Efficiency	89.4	92.8	93.2	92.7	91.9	90.8	91.9
Speed	3580	3561	3539	3516	3491	3465	3491
Line amperes	6.81	9.54	13.1	16.95	20.9	25.31	20.9


ABB Motors and Mechanical Inc.


WINDING # 37WGR601

Typical performance - not guaranteed values.


15 HP 3 PH 60 HZ 3515 RPM 460 V 3756M

TORQUES (LB-FT): PO=112 PU=43.2 LR=62 LRA=161







CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1