

# ABB BALDOR RELIANCE III

---

## Customer information packet

### SPM3543

.75HP, 1175RPM, 3PH, 60HZ, 56H, 3526M, TEFC, F1

Class - None

Division - Not Applicable

**Specifications**

|                                       |                                                             |
|---------------------------------------|-------------------------------------------------------------|
| <b>Enclosure</b>                      | TEFC                                                        |
| <b>Frame</b>                          | 56H                                                         |
| <b>Frame Material</b>                 | Steel                                                       |
| <b>Frequency</b>                      | 60.00 Hz                                                    |
| <b>Haz Area Class and Group</b>       | None                                                        |
| <b>Haz Area Division</b>              | Not Applicable                                              |
| <b>Motor Letter Type</b>              | Three Phase                                                 |
| <b>Output @ Frequency</b>             | .750 HP @ 60 HZ                                             |
| <b>Phase</b>                          | 3                                                           |
| <b>Synchronous Speed @ Frequency</b>  | 1200 RPM @ 60 HZ                                            |
| <b>Voltage @ Frequency</b>            | 230.0 V @ 60 HZ<br>460.0 V @ 60 HZ                          |
| <b>Agency Approvals</b>               | NEMA PREMIUM 4<br>WEEE                                      |
| <b>Ambient Temperature</b>            | 40 °C                                                       |
| <b>Auxiliary Box</b>                  | NO AUXILLARY BOX                                            |
| <b>Auxiliary Box Lead Termination</b> | None                                                        |
| <b>Base Indicator</b>                 | Rigid                                                       |
| <b>Bearing Grease Type</b>            | Polyrex EM (-20F +300F)                                     |
| <b>Blower</b>                         | None                                                        |
| <b>Current @ Voltage</b>              | 1.400 A @ 460.0 V<br>2.800 A @ 230.0 V<br>3.500 A @ 208.0 V |
| <b>Design Code</b>                    | B                                                           |
| <b>Drip Cover</b>                     | No Drip Cover                                               |
| <b>Duty Rating</b>                    | CONT                                                        |
| <b>Efficiency @ 100% Load</b>         | 82.5 %                                                      |
| <b>Electrically Isolated Bearing</b>  | Not Electrically Isolated                                   |
| <b>Feedback Device</b>                | NO FEEDBACK                                                 |
| <b>Front Shaft Indicator</b>          | None                                                        |
| <b>Heater Indicator</b>               | No Heater                                                   |
| <b>High Voltage Full Load Amps</b>    | 1.4 a                                                       |

**Part Detail**

|                     |            |
|---------------------|------------|
| <b>Revision</b>     | B          |
| <b>Type</b>         | AC         |
| <b>Mech. spec.</b>  | 35E6271    |
| <b>Base</b>         |            |
| <b>Status</b>       | PRD/A      |
| <b>Elec. spec.</b>  | 35WGG019   |
| <b>Layout</b>       | 35LYE6271  |
| <b>Eff. date</b>    | 06-07-2024 |
| <b>CD Diagram</b>   | CD0005     |
| <b>Poles</b>        | 06         |
| <b>Leads</b>        | 9#18       |
| <b>Proprietary</b>  | False      |
| <b>Created date</b> | 09-08-2023 |

|                                      |                            |
|--------------------------------------|----------------------------|
| <b>Insulation Class</b>              | <b>F</b>                   |
| <b>Inverter Code</b>                 | <b>Inverter Duty</b>       |
| <b>KVA Code</b>                      | <b>L</b>                   |
| <b>Lifting Lugs</b>                  | <b>No Lifting Lugs</b>     |
| <b>Locked Bearing Indicator</b>      | <b>No Locked Bearing</b>   |
| <b>Max Speed</b>                     | <b>1800 rpm</b>            |
| <b>Motor Lead Quantity/Wire Size</b> | <b>9 @ 18 AWG</b>          |
| <b>Motor Lead Termination</b>        | <b>Flying Leads</b>        |
| <b>Motor Standards</b>               | <b>NEMA</b>                |
| <b>Motor Type</b>                    | <b>3526M</b>               |
| <b>Mounting Arrangement</b>          | <b>F1</b>                  |
| <b>Number of Poles</b>               | <b>6</b>                   |
| <b>Overall Length</b>                | <b>12.91 IN</b>            |
| <b>Power Factor</b>                  | <b>60</b>                  |
| <b>Product Family</b>                | <b>General Purpose</b>     |
| <b>Pulley End Bearing Type</b>       | <b>Ball</b>                |
| <b>Pulley Face Code</b>              | <b>Standard</b>            |
| <b>Pulley Shaft Indicator</b>        | <b>Standard</b>            |
| <b>Rodent Screen</b>                 | <b>None</b>                |
| <b>RoHS Status</b>                   | <b>ROHS COMPLIANT</b>      |
| <b>Service Factor</b>                | <b>1.15</b>                |
| <b>Shaft Diameter</b>                | <b>0.625 IN</b>            |
| <b>Shaft Ground Indicator</b>        | <b>No Shaft Grounding</b>  |
| <b>Shaft Rotation</b>                | <b>Reversible</b>          |
| <b>Shaft Slinger Indicator</b>       | <b>No Slinger</b>          |
| <b>Speed</b>                         | <b>1175 rpm</b>            |
| <b>Speed Code</b>                    | <b>Single Speed</b>        |
| <b>Starting Method</b>               | <b>Direct on line</b>      |
| <b>Thermal Device - Bearing</b>      | <b>None</b>                |
| <b>Thermal Device - Winding</b>      | <b>None</b>                |
| <b>Vibration Sensor Indicator</b>    | <b>No Vibration Sensor</b> |
| <b>Winding Thermal 1</b>             | <b>None</b>                |
| <b>Winding Thermal 2</b>             | <b>None</b>                |

**Nameplate**

| NP4423A01A01L |               |       |        |         |      |               |      |    |       |      |      |   |  |
|---------------|---------------|-------|--------|---------|------|---------------|------|----|-------|------|------|---|--|
| CAT #         | SPM3543       |       |        |         |      | WGT           | 41   |    | LBS   |      |      |   |  |
| SPEC          | 35E6271G019   |       |        |         |      | ENCL          | TEFC |    |       |      |      |   |  |
| SER #         |               |       |        |         |      | CC            | 010A |    | IP    | 54   |      |   |  |
| HP            | .75           |       |        | MAG CUR |      |               | 2/1  |    |       |      |      |   |  |
| VOLTS         | 230/460       |       |        |         |      | NEMA NOM. EFF |      |    |       |      | 82.5 |   |  |
| AMPS          | 2.8/1.4       |       |        |         |      |               | PF   | 60 |       |      |      |   |  |
| RATING        | 40C AMB-CONT  |       |        |         |      |               |      |    |       |      |      |   |  |
| RPM           | 1175          |       |        |         |      | MAX RPM       |      |    | 1800  |      |      |   |  |
| FRAME         | 56H           |       | HZ     | 60      |      | CODE          | L    |    | CLASS | F    |      |   |  |
| SER.F.        | 1.15          |       | SF AMP | 3/1.5   |      |               |      | PH | 3     |      | DES  | B |  |
| DE            | 6205          |       |        | ODE     |      | 6203          |      |    |       |      |      |   |  |
| LUBRICATION   | POLYREX EM    |       |        |         |      |               |      |    |       |      |      |   |  |
| ID LOGO       | INVERTER TYPE |       |        |         | VPWM |               | CHP  | 60 |       | TO   | 90   |   |  |
| ID LOGO       | WK2           | 0.189 |        | CT      | 6    |               | TO   | 60 |       | 10:1 |      |   |  |
| ID LOGO       | SL HZ         | 1.57  |        | VT      | 3    |               | TO   | 60 |       | 20:1 |      |   |  |
|               |               |       |        |         |      |               |      |    |       |      |      |   |  |
|               |               |       |        |         |      |               |      |    |       |      |      |   |  |
|               |               |       |        |         |      |               |      |    |       |      |      |   |  |
|               |               |       |        |         |      |               |      |    |       |      |      |   |  |
|               |               |       |        |         |      |               | QR   |    |       |      |      |   |  |
| YR            |               |       |        |         |      |               |      |    |       |      |      |   |  |

**AC Induction Motor Performance Data**

Record # 100851

Typical performance - not guaranteed values

| Winding: 35WGG019-R017 |    |         | Type: 3526M                              |                     | Enclosure: TEFC           |           |              |
|------------------------|----|---------|------------------------------------------|---------------------|---------------------------|-----------|--------------|
| Nameplate Data         |    |         | 460 V, 60 Hz:<br>High Voltage Connection |                     |                           |           |              |
| Rated Output (HP)      |    | .75     | Full Load Torque                         |                     | 3.34 LB-FT                |           |              |
| Volts                  |    | 230/460 | Start Configuration                      |                     | direct on line            |           |              |
| Full Load Amps         |    | 2.8/1.4 | Breakdown Torque                         |                     | 11.9 LB-FT                |           |              |
| R.P.M.                 |    | 1175    | Pull-up Torque                           |                     | 7.1 LB-FT                 |           |              |
| Hz                     | 60 | Phase   | 3                                        | Locked-rotor Torque |                           | 8.6 LB-FT |              |
| NEMA Design Code       |    | B       | KVA Code                                 |                     | L                         |           |              |
| Service Factor (S.F.)  |    | 1.15    | Starting Current                         |                     | 9.1 A                     |           |              |
| NEMA Nom. Eff.         |    | 82.5    | Power Factor                             |                     | 60                        |           |              |
| Rating - Duty          |    | 40C     | AMB-CONT                                 |                     | Temp. Rise @ Rated Load   |           | 35°C         |
| S.F. Amps              |    | 3/1.5   |                                          |                     | Temp. Rise @ S.F. Load    |           | 40°C         |
|                        |    |         |                                          |                     | Locked-rotor Power Factor |           | 48.3         |
|                        |    |         |                                          |                     | Rotor inertia             |           | 0.189 lb-ft² |

**Load Characteristics 460 V, 60 Hz, 0.75 HP**

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 25   | 39   | 51   | 60   | 66   | 71   | 64   |
| Efficiency      | 68.1 | 78.7 | 81.8 | 82.8 | 82.2 | 80.9 | 82.4 |
| Speed           | 1194 | 1189 | 1183 | 1176 | 1169 | 1161 | 1172 |
| Line amperes    | 1.05 | 1.14 | 1.26 | 1.42 | 1.61 | 1.84 | 1.53 |

ABB Motors and Mechanical Inc.

WINDING # 35WGG019

Typical performance - not guaranteed values.

0.75 HP 3 PH 60 HZ 1175 RPM 460 V 3526M

TORQUES (LB-FT): PO=11.9 PU=7.1 LR=8.6 LRA=9.1





