

ABB BALDOR RELIANCE III

Customer information packet

SPM3615T-G

5HP, 1755RPM, 3PH, 60HZ, 184T, 3648M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	184T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	13.200 A @ 230.0 V 6.600 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	6.6 a
Insulation Class	F

Part Detail

Revision	B
Type	AC
Mech. spec.	36P493
Base	
Status	PRD/A
Elec. spec.	36WGZ629
Layout	36LYP493
Eff. date	09-30-2026
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	04-02-2025

Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3648M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	18.48 IN
Power Factor	78
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1755 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L														
CAT #	SPM3615T-G					WGT	101		LBS					
SPEC	36P493Z629					ENCL	TEFC							
SER #						CC	010A		IP	54				
HP	5		MAG CUR			6.6/3.3								
VOLTS	230/460					NEMA NOM. EFF					91			
AMPS	13.2/6.6					PF	78							
RATING	40C AMB-CONT													
RPM	1755					MAX RPM		2700						
FRAME	184T	HZ		60		CODE	J	CLASS		H				
SER.F.	1.25	SF AMP		15.8/7.9			PH	3	DES	A				
DE	6206		ODE		6205									
LUBRICATION	POLYREX EM													
ID LOGO	INVERTER TYPE			VPWM		CHP	60		TO	90		1.5:1		
ID LOGO	WK2	0.447	CT	6	TO	60	10:1							
ID LOGO	SL HZ	1.5	VT	3	TO	60	20:1							
							QR							
YR														

AC Induction Motor Performance Data

Record # 112300

Preliminary Data Sheet

Winding: 36WGZ629-R012			Type: 3648M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		5	Full Load Torque		14.97 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		13.2/6.6	Breakdown Torque		56.6 LB-FT		
R.P.M.		1755	Pull-up Torque		31.6 LB-FT		
Hz	60 Phase	3	Locked-rotor Torque		35.4 LB-FT		
NEMA Design Code		B	KVA Code		J	Starting Current	53.4 A
Service Factor (S.F.)		1.25	No-load Current		3.26 A		
NEMA Nom. Eff.		91	Power Factor		78	Line-line Res. @ 25°C	2 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		57°C
S.F. Amps		15.8/7.9	Temp. Rise @ S.F. Load		76°C		
			Locked-rotor Power Factor		38.4		
			Rotor inertia		0.447 lb-ft²		

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	39	60	72	79	82	84	82
Efficiency	85.8	90.6	91.4	91.1	90.3	89.1	90.3
Speed	1790	1780	1770	1759	1747	1734	1747
Line amperes	3.59	4.33	5.33	6.55	7.91	9.4	7.91


ABB Motors and Mechanical Inc.

WINDING # 36WGZ629

Typical performance - not guaranteed values.




5 HP 3 PH 60 HZ 1755 RPM 460 V 3648M

TORQUES (LB-FT) : PO=56.6 PU=31.6 LR=35.4 LRA=53.4





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
900000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005