

ABB BALDOR RELIANCE III

Customer information packet

SUM21004-4

10HP, 1765RPM, 3PH, 60HZ, 210TY, TENV, V1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	210TY
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Phase	3
Agency Approvals	CCSA US
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Heater Indicator	No Heater
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	IP68
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	V1
Number of Poles	4
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	1.437 IN
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Starting Method	Direct on line
Thermal Device - Winding	Normally Closed Thermostat

Part Detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	86077
Layout	619738-003
Eff. date	12-10-2024
CD Diagram	416820-001
Poles	///
Leads	
Proprietary	False
Created date	07-22-2021

Nameplate

000692000MB		
SUITABLE FOR OPERATION ON PWM		
INVERTER EQUIPPED WITH IGBT		
DEVICES AND CAPABLE OF		
CARRIER		
FREQUENCY OF 2 KHZ MINIMUM		

000613007MS

CAT.NO.	SUM21004-4		SPEC NO.		S21-CWS0-0004			
SER.NO.				FRAME SIZE	210TY			
	HP	RPM	VOLTS	AMPS	HZ	S.F.		
	10	1765	230/460	25/12.5	6-60	1.00		
	10	1765	230/460	25/12.5	60	1.15		
CONSTANT HP RPM		@		HZ	CODE	H		
TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT	DESIGN	B
D.E. BRG.	60BC02JPP30A		ENCL	TENV	DUTY	15MIN	PH	3
O.D.E. BRG.	30BC02JPG30A		MOTOR WEIGHT				AMB	40
	FINAL CONN VOLTAGE = 460 *15							
	MIN IN AIR							

000613007MS

CAT.NO.	SUM21004-4		SPEC NO.		S21-CWS0-0004			
SER.NO.				FRAME SIZE	210TY			
	HP	RPM	VOLTS	AMPS	HZ	S.F.		
	10	1765	230/460	25/12.5	6-60	1.00		
	10	1765	230/460	25/12.5	60	1.15		
CONSTANT HP RPM		@		HZ	CODE	H		
TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT	DESIGN	B
D.E. BRG.	60BC02JPP30A		ENCL	TENV	DUTY	15MIN	PH	3
O.D.E. BRG.	30BC02JPG30A		MOTOR WEIGHT				AMB	40
	FINAL CONN VOLTAGE = 460 *15							
	MIN IN AIR							

Record #86077 - Typical performance - not guaranteed values

Winding	07WGA0017
Type	0738M
Enclosure	TENV

Nameplate data

Rated Output	10		
Volts	230/460		
Full Load Amps	25/12.5		
R.P.M.	1765		
Hz	60	Phase	3
KVA Code	H		
S.F.	1.15		
NEMA Nom. Eff.	90.2	Power Factor	82
Duty	15 MIN		
S.F. Amps			

460 V, 60 Hz:

High Voltage Connection

Full Load Torque	29.74 LB-FT
Start Configuration	direct on line
Breakdown Torque	83.88 LB-FT
Pull-up Torque	29.9 LB-FT
Locked-rotor Torque	45.11 LB-FT
Starting Current	87.77 A
No-load Current	4.92
Line-line Res. @ 25°C	1.25 Ω
Temp. Rise @ Rated Load	15°C
Temp. Rise @ S.F. Load	18°C
Locked-rotor Power Factor	37.1
Rotor inertia	0.934 lb-ft ²

Load Characteristics 460 V, 60 Hz, 10 HP


% of Rated Load	NL	25	50	75	100	125	150	SF
Power Factor	6	47	68	78	82	84	84	83
Efficiency	0	88.1	90.8	91.9	90.9	90	88.6	90.4
Speed	1799	1792	1785	1777	1768	1758	1747	1762
Line amperes	4.92	5.73	7.53	9.86	12.49	15.44	18.79	14.3

SPEED TORQUE / SPEED CURRENT CURVES


BALDOR • RELIANCE

07WGA0017

10HP 460V 60HZ





Record: 86077



416820-001

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 9 LEAD Y CONNECTED



(N. P. 1575-A)




REV. DESC: FONT CHANGE FOR PDF SEARCHABLE		
REV. LTR: A	VERSION: 01	TDR: 000001009382
FILE: \MGA\00000\659	REVISED: 10: 33: 07 12/21/2016	BY: MGHMTT
MTL: —		

BALDOR

CONN DIAG — STANDARD 9 LEAD, Y CONNECTED
SH 1 of 1

416820-001

CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
S00000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005