

ABB BALDOR RELIANCE III

Customer information packet

VXM05162

1//.75HP, 1155//970RPM, 3PH, 60//50HZ, 56C, 3

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	56C
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ .750 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.500 A @ 208.0 V 3.200 A @ 190.0 V 3.000 A @ 230.0 V 1.600 A @ 380.0 V 1.500 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT

Part Detail

Revision	D
Type	AC
Mech. spec.	35Q643
Base	
Status	PRD/A
Elec. spec.	35WGG019
Layout	35LYQ643
Eff. date	05-27-2026
CD Diagram	CD0005
Poles	06
Leads	9#18
Proprietary	False
Created date	02-23-2023

Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.5 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3526M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	15.12 IN
Power Factor	67
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1155 rpm 970 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP0887XPSL												
NO.							CC					
S/N							TEMP CODE	T3C				
SPEC.	35Q643G019						INV.TYPE	PWM				
CAT.NO.	VXM05162						C HP FR	60	C HP TO	90		
HP	1//.75						CT HZ FROM	6	CT HZ TO	60		
VOLTS	230/460//190/380						VT HZ FROM	6	VT HZ TO	60		
AMPS	3/1.5//3.2/1.6				MAG CUR		2/1					
RPM	1155//970				MX RPM		1800					
HZ	60//50	PH	3	CL	F	NOM.EFF.	82.5					
SER.F.	1.00	DES	B	SL HZ	1.5	WK2	0.189					
FRAME	56C	RATING		40C AMB-CONT								
	NEMA MG-1 PART 5, IP54											
	1.15 SF ON SINE WAVE											

AC Induction Motor Performance Data

Record # 73789

Typical performance - not guaranteed values

Winding: 35WGM497-R087			Type: 3526M		Enclosure: XPFC			
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		1//.75		Full Load Torque		4.51 LB-FT		
Volts		230/460//190/380		Start Configuration		direct on line		
Full Load Amps		3.6/1.8//3.4/1.7		Breakdown Torque		15.23 LB-FT		
R.P.M.		1155//960		Pull-up Torque		11.1 LB-FT		
Hz		60//50	Phase	3	Locked-rotor Torque		11.9 LB-FT	
NEMA Design Code		B		KVA Code	K	Starting Current		10.8 A
Service Factor (S.F.)		1		No-load Current		1.21 A		
NEMA Nom. Eff.		82.5	Power Factor		64	Line-line Res. @ 25°C		16.1 Ω
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		48°C
						Locked-rotor Power Factor		41.5
						Rotor inertia		0.155 LB-FT2

Load Characteristics 460 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	28	44	56	65	71	75
Efficiency	66	77	80.7	81.4	80.9	79.5
Speed	1190	1180	1170	1158	1145	1129
Line amperes	1.25	1.37	1.54	1.77	2.04	2.35


ABB Motors and Mechanical Inc.


WINDING # 35WGM497

Typical performance - not guaranteed values.




1 HP 3 PH 60 HZ 1158 RPM 460 V 3526M

TORQUES (LB-FT): PO=15.23 PU=11.1 LR=11.9 LRA=10.8





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
900000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005