

BHP-Series, Cross Bearing Puller Sets

ENERPAC 

▼ Shown: Cross Bearing Puller Set BHP361G



- Precise hydraulic control allows fast, efficient and safe pulling
- High-quality, forged steel components provide superior reliability and service.

BHP Series

Capacity:

6, 11, 16 and 22 ton

Reach:

357 - 864 mm

Spread:

260 - 580 mm

Maximum Operating Pressure:

350 bar



CAUTION! Not all puller components and configurations are rated at the set capacity. Please contact Enerpac for details.

Cross Bearing Puller Sets

		
Hand Pump	XA11G Air-Hydraulic Foot Pump	PUD1300E Electric Pump
BHP162 BHP261G BHP361G BHP561G	BHP162A BHP261GA BHP361GA BHP561GA	BHP162EE * BHP261GEE * BHP361GEE * BHP561GEE *

* E = 230 V pump. For 115 V change "E" suffix into "B".

▼ SELECTION CHART

Cross Bearing Puller Set Capacity		6 ton	11 ton	16 ton	22 ton
	Model Number ►	BHP162 ¹⁾	BHP261G	BHP361G	BHP561G
Included Hydraulics	Set Weight ►	26 kg	62 kg	121 kg	185 kg
• Hand Pump		P142	P392	P392	P80
• Cylinder		RWH121900	RCH202	RCH302	RCH603
• Saddle		–	HP2015	HP3015	HP5016
• Hose		HC7206C	HC7206C	HC7206C	HC7206C
• Gauge + Adaptor		GA45GC	GA45GC	GA45GC	GA45GC
20 Cross Bearing Puller ²⁾	Model Number ►	BHP1772	BHP262	BHP362	BHP562
Spread (mm)	Maximum	260	345	440	580
	Minimum	115	140	180	220
Reach (mm)	Maximum	357	570	710	864
Adjusting Screw	Diameter	¾" - 16 UNF	1" - 8 UNC	1¼" - 7 UNC	1½" - 5.5 UNS
	Length	400	675	795	975
Leg (mm)	Length	105	239	203	609
	Length	357	419	457	863
	Length	–	571	711	–
	Length	–	114	–	–
Upper Leg Ends	Thread	¾" - 16 UNF	¾" - 16 UNF	1" - 14 UNS	1¼" - 12 UNF
Lower Leg Ends	Thread	5/8" - 18 UNF	5/8" - 18 UNF	1" - 14 UNS	1¼" - 12 UNF
30 Bearing Cup Puller ²⁾	Model Number ►	BHP180	BHP280	BHP380	BHP580
40 Bearing Separator ²⁾	Model Number ►	BHP181	BHP282	BHP382	BHP582
• Wooden Case		CM6	CW187	CW350	CW750

¹⁾ Includes Adaptor FZ1055.

²⁾ Can be ordered separately without hydraulic components, see next page.