

▼ Shown: Grip Puller Set BHP351G



- Precise hydraulic control allows fast, efficient and safe pulling
- High-quality, forged steel components provide superior reliability and service
- Available with and without full hydraulic set.

BHP Series



Capacity:

14, 24, 36 and 50 tons

Reach:

9.92 - 27.56 inches

Spread:

9.84 - 43.30 inches

Maximum Operating Pressure:

10,000 psi

Ordering Example

Model Number BHP251G:

includes Grip Puller BHP252 and a full hydraulic set. (Hand pump, cylinder, saddle, hose, gauge and gauge adaptor).

Model Number BHP252:

includes Grip Puller mechanical parts **only**, for use with your existing hydraulics.

▼ SELECTION CHART

Grip Puller Set Capacity **		14 tons	24 tons	36 tons	50 tons ***	
Model Number ►		BHP152 ¹⁾	BHP251G	BHP351G	BHP551G	
Included Hydraulics	Set Weight ►	48 lbs	123 lbs	200 lbs	353 lbs	
• Hand Pump		P142	P392	P392	P80	
• Cylinder		RWH121900	RCH202	RCH302	RCH603	
• Saddle		–	HP2015	HP3015	HP5016	
• Hose		HC7206C	HC7206C	HC7206C	HC7206C	
• Gauge + Adaptor		GA45GC	GA45GC	GA45GC	GA45GC	
10	Grip Puller	Model Number ►	BHP1762 *	BHP252 *	BHP352 *	BHP552 *
Maximum Spread (inches)	2-jaw		9.84	15.75	23.38	35.43
	3-jaw		9.84	19.68	31.50	43.30
Maximum Reach (inches)	2-jaw		9.92	11.81	15.25	27.56
	3-jaw		9.92	11.81	15.25	27.56
Jaw (inches)	Thickness		0.59	0.79	0.98	1.18
	Width		0.94	1.10	1.50	1.57
Adjusting Screw (inches)	Thread		¾" - 16 UNF	1" - 8 UNC	1¼" - 7 UNC	1½" - 5.5 UNS
	Length		15.75	26.38	31.16	38.39
• Case			CW166	CW166	CW350	CW750

¹⁾ Includes Adaptor FZ1055.

* Grip Puller order number without hydraulics.

** See warning on page 158.

*** Puller capacity at 7,850 psi; maximum cylinder capacity at 10,000 psi is 60 tons.