

▼ THQ706T



Twin Torque Wrench Hose

- Thermo-plastic safety dual hoses
- For use S, W, RSL, DSX and HMT-Series torque wrenches and 10,000 psi torque pumps
- With 1/4" Spin-on Torque Wrench Couplers
- For demanding applications, featuring a 4:1 safety factor
- Maximum working pressure of 10,000 psi
- Outside jacket is polyurethane, to provide maximum abrasion resistance
- Low volumetric expansion under pressure to enhance overall system efficiency
- Crimped-on vinyl strain relief for improved life and durability on all models.

Use the THQ-Series hoses with Enerpac torque wrenches and pumps to ensure the integrity of your hydraulic system. ►

THQ
Series

Hose Lengths:
6 - 19.5 - 39 feet

Maximum Operating Pressure:
10,000 psi / 700 bar



HT, B-Series, Hoses and Fittings for Tensioning 21,750 psi
Bolt tensioning equipment require different hoses, couplers and fittings than torque wrenches and pumps.

Page: 307



Premium Hydraulic Oil
Use only genuine Enerpac Hydraulic Oil. The use of any other fluid will render your Enerpac warranty null and void.

Page: 140



Internal Diameter	Hose Length	Model Number	Maximum Operating Pressure	Hose Ends 1/4" Spin-on Torque Wrench Couplers		 (lbs)
				Hose end one	Hose end two	
0.25 (inch)	6.0 (ft)	THQ702T	10,000 (psi)	female half TR630 + male half TH630	male half TH630 + female half TR630	4.9
	19.5	THQ706T	10,000	female half TR630 + male half TH630	male half TH630 + female half TR630	9.9
	39.0	THQ712T	10,000	female half TR630 + male half TH630	male half TH630 + female half TR630	16.8